Mini Filter / Regulator - P31

Symbols



- Integral 1/4" ports (NPT, BSPP & BSPT)
- High efficiency 5 micron element as standard
- Excellent water removal efficiency
- Robust but lightweight aluminum construction
- Positive bayonet latch to ensure correct & safe fitting

  Secondary pressure ranges 0-2 bar (0-30 psig), 0-4 bar, (0-60 psig), 0-8 bar (0-125 psig)
- Secondary aspiration plus balanced poppet provides quick response and accurate pressure regulation

Options:

P 3 1	E A			E				N		P

Thread type

BSPP	1
BSPT	2
NPT	9

Port size

1/8	1
1/4	2

Element

5µ Element	E

Bowl type

Poly bowl with bowl guard	G
Metal bowl without sight gauge	M

Drain type

Pulse drain	B
Manual drain	M

Relief

Relieving	B
Non relieving	N

Adjustment range

With square gauge		With round gauge		Without guage	
2 bar (0.2 MPa)*	2	2 bar (0.2 MPa)	Z	2 bar (0.2 MPa)	Y
4 bar (0.4 MPa)*	4	4 bar (0.4 MPa)	M	4 bar (0.4 MPa)	L
8 bar (0.8 MPa)**	6	8 bar (0.8 MPa)	G	8 bar (0.8 MPa)	N

Mounting

Plastic panel mount nut	P